

Trevor Woodcock
Managing Director

Phone: +44 (0) 207 078 8123

Fax: +44 (0) 1252 514 578

Mobile & WhatsApp: +44 (0) 7958 298 959

Skype: trevor_woodcock

EXPORTIZE



www.exportize.co.uk

Westmead House, Farnborough, Hampshire GU14 7LP

5W30 FS V

Fully synthetic low SAPS engine oil

Product code: M404

Product Description:

5W30 FS V is a new generation fully synthetic low SAPS (sulphated ash, phosphorus and sulphur) multigrade engine oil formulated using the latest developments in synthetic technology together with state of the art additive chemistry which sets new standards in engine oil performance.

5W30 FS V has been developed to provide outstanding performance, e.g. in terms of engine cleanliness and fuel economy benefits, along with effective emission control and full compatibility with emission control aftertreatment systems such as diesel particulate filters. Low SAPS additive technology ensures a high level of continuous pollution control thereby minimising environmental damage.

Benefits:

- Effective environmental protection
- Ensures lubricant performance over extended drain intervals
- Effective fuel efficiency
- Very high standards of engine cleanliness
- Exceptional long term anti-wear and oxidation stability
- Excellent high and low temperature performance
- Exceptional long term additive response

Applications:

5W30 FS V is suitable for both petrol and diesel engines, including turbocharged, and is formulated to meet the performance demands and requirements of the most up to date VW/Audi specifications VW 504.00 and VW 507.00 which encompass high standards of emission control and ultimate engine protection. In addition, 5W30 FS V is suitable for use in a wide range of passenger cars and light commercial vehicles (including many Honda, Hyundai, Kia, Nissan, Subaru and Toyota) where the following specifications are required.

Note: 5W30 FS V is backwards compatible with most other VW specifications and you are encouraged to call our technical help line for advice on this issue.

Product Specification:

ACEA- C2, C3, A3/B4-04

VW- 504.00/507.00

BMW- LL-04

MB- 229.51

Porsche- C30

JASO- DL-1

Typical Test Data:

Kinematic Viscosity @ 100°C (cSt)- 11.8

Kinematic Viscosity @ 40°C (cSt)- 72.3

Viscosity index -160

CCS @ -30°C (cP)- 6080

Sulphated Ash (% w/w)- 0.60

Flash Point COC (°C) -212

TBN (mg KOH / g)- 6.00

Health & Safety:

Please refer to the relevant health and safety data sheet, a copy of which is freely available to all of our customers.

Availability:

5W30 FS V is available in bulk road tanker deliveries, 205 litre barrels and 25 litre drums.